






LTC -A2001N



Features

- ※ H.264 compression
- ※ Support dual stream to output both for full view and tracking image
- ※ Compatible with ONVIF,RTSP,RTMP protocols
- ※ Configuration of camera is realized by network
- ※ Come with face and motion detection tracking technology,precisely lock & track lecturer
- ※ Standalone tracking,there is no need to have extra devies/sensors
- ※ Both two lens can output up to 1080p30 images through network
- ※ Smart full view lens has addressed geometric distortion
- ※ Color and brightness of both the two lens are the same(only for LTC-A2001N)
- ※ When tracking, the camera image is automatically adaptive to lecturer's height
- ※ There is no limit to tracking zone,the camera can track lecturer all around the classroom
- ※ Smart tracking performance like auto zoom,tilt motion,free of interfering objects/lights

Dimensional Drawing




- | | |
|------------|-------------------|
| ① Audio | ④ HD-SDI 2 |
| ② Network | ⑤ RS-485 / RS-232 |
| ③ HD-SDI 1 | ⑥ Power |

Technical Specification

Model No.	LTC-A2001N
Tracking Camera	
Image Sensor	1/2.8" Exmor CMOS, 2.14MP
Lens	f =4.7mm -94.0mm;F1.6 - F3.5
Zoom	Optical: 20X, Digital: 12X
Field of View	59.5° - 2.9°
Focus	Auto, Manual, One push
Min.Illumination	0.5Lux(Color), 0.1Lux(B/W)
Shutter Speed	1/1 - 1/10,000s
Gain	Auto/Manual
White Balance	Auto, Indoor, Outdoor, One push, Manual,
Exposure	Auto, Manual, Shutter Priority, Iris Priority
S/N Ratio	Above 50dB
Full view camera	
Image Sensor	1/2.8" Exmor CMOS
Effective Pixel	2.14mp
White Balance	Auto
Exposure	Auto
Field of View	Horizontal:92°;Vertical:50°(before geometric distortion correction)
Lens	3.73mm
PTZ	
Pan/Tilt Angle Range	Pan: -170° - +170° ; Tilt: -30° - +90°
Pan/Tilt Speed	Pan: 0.1° - +120°/s ; Tilt: 0.1° - +90°/s
Preset Number	256
Network	
Max,Image Size	1920x1080
Frame Rate	HD:50Hz:25fps(1920x1080) 50fps(1280x720); 60Hz:60fps(1920x1080) ,60fps(1280x720)
Video Compression	H.264
Audio Compression	AAC
Protocol	HTTP,RTSP,RTMP,TCP,UDP,ONVIF
Dual Stream	Support
Simultaneous Users	up to 10 users
Ethernet	RJ45 connector, 100M
Comm.Interface	RS-485, RS-232
Protocol	VISCA and PELCO-D
General	
Power Supply	DC12V
Power Consumption	<20W
Working Temp	0°C - +40°C
Storage Temp	-20°C - +60°C
Dimension	226mm x 212mm x 163mm
Weight	1.96KG
Color	Grey

Technical Specification



Wall Bracket



Ceiling mount

*** Product specification are subject to change without notice ***